


**Contaminated Sediments  
In-Situ Treatment Technologies  
Workshop**

**Baltimore, MD – February 18 & 19, 2004**

Craig Zeller, P.E.  
Remedial Project Manager  
US EPA – Region 4  
404.562.8827

[Zeller.Craig@epa.gov](mailto:Zeller.Craig@epa.gov)



# Ashley River

- Tidally influenced – range 5 to 6 feet
- PAH & creosote contamination with depth
- Area of Potential Ecological Concern (APEC)  
= 3 acres
  - 1,500 feet of near shore sediment/100 feet wide
  - Former 30 feet deep navigation channel
  - No specific cleanup # issued
  - Defined area & Performance Standards

# Plan A – Enhanced Sedimentation

- Short term effectiveness during construction
- Provide cover to mitigate contact/transfer to food chain
- Long term effectiveness/permanence




Figure 7: Areas of sediment accumulation after 4 days - Dike Plan

# Constructability Concerns

- Geotechnical limitations/steep slopes
- Affected property owner
- Existing structures

# Plan B – Engineered Subaqueous Cap


- Non woven Geotextile
  - Consolidation concerns
  - Thickness monitoring
- 12 inch minimum thickness
  - 18 inches placed
- Property owner objection
  - 2 ft elevation increase would limit access
  - Spud Barge traffic impacts on cover
  - Institutional controls? ...no thanks

# Plan C



- 2 acre subaqueous sand/geotextile cap
- 1 acre solidified/stabilized by Williams Environmental



# Sand Cap/Solidification Plan View



# Cap Cross Sections



# Solidification/Stabilization Benefits

- Solidified sediment less permeable than sand
- Minimal elevation increase (+ 4 to 6 inches)
- Forms more cohesive layer to withstand erosion
- Allowed spud barge operation



# In-Situ S/S Methodology

- Upper 2 feet mixed with cement-based grout + proprietary chemical
- Wide tracked excavator with floatation hull
- Tubular injector with four mixing tines and manifold
- Quick cure time created a “work” platform
- Reagents fed through hoses from upland batch plant
- Work hours two hrs. each side of low tide(s)



# Work Summary

- 181,303 gallons of reagent
  - 632 tons cement
  - 3,971 gallons of proprietary chemical
  - 160,000 gallons of water
- 33,000 square feet x 2 feet depth = 2,450 CY
- 35 work days
- Total Cost = \$561,154 (\$230/CY)

























# Acknowledgements

Mark Fleri, P.E.

Williams Environmental Services, Inc.

2075 West Park Place

Stone Mountain, GA 30087

770.879.4831

[mfleri@wmsgrpintl.com](mailto:mfleri@wmsgrpintl.com)

Mike Slenska, P.E.

Beazer East, Inc.

One Oxford Centre, Suite 3000

Pittsburg, PA 15219

412.208.8867

[slenskam@hansonle.com](mailto:slenskam@hansonle.com)

Tom deGroot

Remedius, LLC

2810 Duniven Circle, Suite 102

Amarillo, TX 79109

806.457.0800

[tjdegroot@remedius.com](mailto:tjdegroot@remedius.com)