




# *Demonstration and Installation of MTBE Biobarriers at Naval Base Ventura County, Port Hueneme, CA*

Karen Miller  
Naval Facilities Engineering Service Center  
[karen.miller1@navy.mil](mailto:karen.miller1@navy.mil)

Dr. Paul Johnson  
Arizona State University  
[paul.c.johnson@asu.edu](mailto:paul.c.johnson@asu.edu)




# Biobarrier Technology Overview



Treatment of MTBE-contaminated aquifers through:

- inoculation with MTBE-degrading organisms (MC-100 and SC-100)
- aeration/oxygenation of the aquifer



*Apply biobarrier technology to a mixed MTBE-BTEX dissolved plume*



# NBVC, Port Hueneme, CA



← N




# *Demonstration System Design*



- (1) Treatment system must not alter the natural flow path**
- (2) Modular and flexible with respect to operating conditions.**


- (1) Close well spacing**
- (2) Injection at two depths**
- (3) Pulsed gas injection (air and O<sub>2</sub>)**  
**[trapped gas supplies oxygen for days after injection]**




# Biobarrier Subsurface Features




## Subsurface Features






# MTBE Distribution




# TBA Concentrations




March 2002



October 2002



Groundwater flow



# *Final Remedy Options for NBVC*




# *Installation of Two Additional Biobarriers*



- **Installation Costs:**  
\$500K to install two additional biobarriers (a 400 foot wide and a 500 foot biobarrier)
- **O&M Costs:**  
\$125K/year
- **Advantage:**
  - Completely contains MTBE plume
  - Protects against future spills
  - No groundwater or other disposal costs



# MTBE Biobarrier Diagram




# *Leading Edge Biobarrier*



- 400 feet wide biobarrier
- Wells on 8 foot spacing (96 wells)
- Multi-level injection depth


# MTBE Isoconcentration Contour Map, October 2004



# **Status of NBVC Biobarriers, Oct 2004**



- Eleven wells sampled along the lateral boundaries of the historical MTBE plume indicate that the lateral extent of the plume is remaining relatively stable.
- The monitoring data indicates that the leading-edge biobarrier is effectively containing the MTBE plume.
- The Navy is planning to shut down the pump and treat system after receiving approval from the Los Angeles Regional Water Quality Control Board.





*Prediction of Groundwater Quality Improvement  
Down-Gradient of In-Situ Permeable Treatment  
Barriers and Fully Remediated Source Zones*

NFESC POC: Laura Yeh


ASU Investigators: Paul Dahlen, Pamela Maass,  
Dr. Paul Johnson



# Technical Objective




Test our ability to anticipate changes in down-gradient water quality with time for permeable reaction barriers (PRB) that bisect dissolved plumes



## *PRB Performance Monitoring & Issues*

- Ideally, a PRB is installed at the leading edge of a plume; however, other factors may dictate its placement up-gradient - thereby bisecting the plume.
- Performance of PRB systems is generally determined by monitoring up- and down-gradient concentrations as well as concentrations in the treatment zone, and then looking for changes between them.




# Background



## PRB Performance Monitoring & Issues

Based on empirical observations, groundwater quality down-gradient of PRB's rarely responds as quickly as anticipated based on concentrations measured in the treatment zone and conventional groundwater travel time/modeling estimates.

This can lead some to conclude that the system is “not working”.




# Field Site




NBVC Port Hueneme was chosen because:

- The site is already reasonably well-characterized
- There is a well-understood large-scale PRB, with extensive operating data, an accessible GeoProbe unit, and shallow groundwater.
- MTBE is a reasonable surrogate for other relatively recalcitrant chemicals




System start-up Sept. 2000  
Groundwater velocity: 1 ft/d

# Field Work - Year 1




# Initial Plume...

Recreated from pre-demonstration EM6-X concentrations and limited well data




# **Year 1 Field Work**

## *Concentrations at 11 ft BGS (April + July data)*




# ***Year 1 Field Work***

### *Concentrations at 13 ft BGS (April + July data)*




# **Year 1 Field Work**

## Concentrations at 17 ft BGS (April + July data)



# **Year 1 Field Work**


## Concentrations along plume centerline (vertical slice) (April + July data)



# Transition Plan



- Disseminate results to RPMs via NFESC's Technology Transfer Program (RITS, RPM newsletters, web page).
- Final Report to be "how to" manual with example and any new calculation tools developed from this work.
- Peer reviewed Journal article
- Workshop/presentation/poster (as desired), at the end of the project to be presented at the SERDP/ESTCP Symposium, Tri-Service Environmental Conference or a Battelle conference.



# Publications



- Johnson, P.C., K.D. Miller, and C.L. Bruce 2004. A Practical Approach to the Design, Monitoring, and Optimization of In-Situ MTBE Aerobic Biobarriers. *NFESC Technical Report TR-2257-ENV*
- Johnson, P.C., K.D. Miller, and C.L. Bruce. 2003. ESTCP Final Report, In-Situ Bioremediation of MTBE in Groundwater. *NFESC Technical Report TR-2222-ENV*
- Miller, K.D., P.C. Johnson and C.L. Bruce. 2003. ESTCP Cost and Performance Report, In-Situ Bioremediation of MTBE in Groundwater. *NFESC Technical Report TR-2216-ENV*

